



MANUFACTURER'S NOTIFICATION FOR M & M INDUSTRIES, INC. UN/DOT PACKAGING FOR HAZARDOUS SOLIDS/LIQUIDS

General Information:

At M&M Industries, we understand your goal to safely transport your valuable products along roads and highways. You want to provide your customers with value while keeping their trust. While we are legally bound to provide you with the following information, M&M Industries also wants you to know we value your endeavor and want to help you reach your goal every day.

Under the **U.S. Department of Transportation's Title 49CFR** it is the **Shipper's Responsibility** to determine that the packaging or container is an authorized packaging, including all part 173 requirements. The selected packaging must be properly assembled for transportation in accordance with the manufacturer's notification. **Please do all testing and research necessary to ensure that you have selected the proper M & M Industries container for use with your product.**

To meet UN/DOT Standards, this package must be properly closed for shipment.

At the time of transfer, the packaging does not meet the UN standard because it is disassembled. Only when assembled as specified in the closing instructions below, and using the components described herein, is this packaging certified to meet the UN standard. Failure to follow the closing instructions or substituting package components with components other than those identified in the following paragraph will render the UN/DOT Certification invalid.

A copy of the manufacturer's notification, including closing instructions, must be made available for inspection by a representative of the Department of Transportation upon request for at least 90 days once the package is offered to the initial carrier for transportation in commerce, as of this time (March 2015). However, M&M Industries recommends that you retain these documents for a minimum of 365 days after the package is offered for shipment. The current record retention requirements are subject to change and are found in 49CFR 173.22(a)(4), <http://www.ecfr.gov>

M&M Industries takes superb pride in our Quality Assurance program and systems. However, even with our absolute best efforts, fittings on covers / pails can become

damaged or shift during transportation or storage after leaving our facility. M&M Industries recommends that fillers/offers take all steps deemed necessary to check the fittings on each pail / cover, to meet your quality standards. An example of this is a screw cap on a cover that may vibrate or back off during transportation. The offeror of a hazardous material may be open to liability if they do not take the necessary precautions. Should you have any questions, please contact customer service at **(800) 331-5305**.

CLOSING INSTRUCTIONS FOR:

Life Latch® Liquid Containers

Identification of Packaging:

This packaging is UN certified for both liquid and solid hazardous materials. For LIQUIDS, only the 5-gallon Life Latch ® Liquid container is UN certified, and it must contain the following gasket:

Lid Size	Gasket Material (Installed in Pail)	Gasket Length	Gasket Diameter	Spout Options
5.0 Gallon	Closed cell Neoprene	36.938"-38.445"	.260"- .340"	Sonically welded Polyethylene American Flange spout #BUB0380000N0112 with 1.50" opening, 2.50" total fitting.

This package type is identified by:

Size	Pail ID Number	Matching Lid ID number	Lid Diameter (ref only, measured at bottom)
5.0 Gallon Liquid Screw Top	11395, 40AQPA	11396, 40AQCA	13.053"



UN Markings for Life Latch® Liquid Containers:

An appropriate UN marking must be maintained for each M&M Industries container design. The UN markings for M&M Industries **Life Latch® Liquid** containers are listed below.

5.0 Gallon Liquid Pail	1H2/Y30/S (for solids) 1H2/Y1.5/30 (for liquids)
------------------------	---

In accordance with the U.S. Department of Transportation’s Title 49CFR, Section 178.2, manufacturers of U.N. Standard/DOT Specification packages are required to notify in writing each person to whom that packaging is transferred of all requirements in this part not met at the time of transfer, and with information specifying the type(s) and dimensions of the closings, including gaskets and any other components needed to ensure that the packaging is capable of successfully passing the applicable performance tests. This information must include any procedures to be followed, including closing instructions for inner packaging’s and receptacles, to effectively assemble and close the packaging for the purpose of preventing leakage in transportation.

Specifically, the following items pertain to the **Life Latch® Liquid** containers:

- **Life Latch® Liquid** containers are certified to the UN/DOT performance-oriented packaging standards and are marked with the appropriate UN markings on the container.

- The **Life Latch® Liquid** pail must always be used with the correct **Life Latch® Liquid lid** to meet the UN/DOT performance-oriented packaging standards.
- **Life Latch® Liquid** containers **are not** UN certified for air transportation.

CLOSING INSTRUCTIONS FOR SOLIDS and LIQUIDS:

Only the 5 Gallon Life Latch® Liquid style container with GASKETED pail is UN certified for liquid and solid hazardous materials. Package components required:

- Appropriately marked UN/Dot certified M&M Industries Pail, gasketed 5 gallon
- Matching lid size with handle attached

To close: Seat lid on top of pail (engraved MM on bottom of pail). Rotate lid counterclockwise until the lid drops down over the threads, once the lid drops over the threads rotate cover clockwise a complete 360 degrees, the square symbol on the bottom outside of the cover should pass the numbers on the side of the pail by a minimum of .500". For ease of application, use the built-in hand lever on the cover. **Inspect lid after application to confirm it is properly seated.**

